





NOTES

- 1. CONCRETE SHALL BE CONCRETE MIX NO. 6 (4500 PSI).
- 2. REINFORCEMENT SHALL BE PLAIN OR EXPOXY COATED 4" X 4" W4.0 X W4.0 WELDED WIRE FABRIC.
- 3. ONE CONNECTOR PIN SHALL BE FURNISHED WITH EACH BARRIER. SEE STD. MD 104.87-11 FOR DETAILS OF CONNECTOR PIN.
- 4. THE APPROACH PLATE SHALL BE FABRICATED USING 1/2" THICK STEEL PLATE BENT OR WELDED TO THE CONFIGURATION SHOWN ON STD. MD 104.87-16 AND GALVANIZED AFTER FABRICATION. THE APPROACH PLATE SHALL BE ANCHORED TO THE PRECAST TEMPORARY BARRIER TRANSITION AND TO THE EXISTING CONCRETE BARRIER IN THE FIELD TO ACHIEVE PROPER PLACEMENT AND HOLE ALIGNMENT WITH 6 EXPANSION ANCHORS (EACH END) AND 1/8" @ HEX HEAD BOLTS.
- 5. THE COST OF THE APPROACH PLATE. ANCHORS. BOLTS. CONNECTOR PIN. LABOR. ETC. SHALL BE INCIDENTAL TO THE UNIT PRICE PER EACH FOR PRECAST TEMPORARY JERSEY SHAPE CONCRETE BARRIER TRANSITION LEFT SIDE APPROACH.

SPECIFICATION CATEGORY CODE ITEMS **Maryland Department of Transportation** 104 STATE HIGHWAY ADMINISTRATION Kik G. MECOLA **APPROVED** STANDARDS FOR HIGHWAYS AND INCIDENTAL STRUCTURES DIRECTOR - OFFICE OF HIGHWAY DEVELOPMENT PRECAST TEMPORARY JERSEY SHAPE CONCRETE APPROVAL • APPROVAL • FEDERAL REVISIONS TRAFFIC BARRIER TRANSITION-LEFT HIGHWAY ADMINISTRATION APPROVAL 11_9_90 APPROVAL 3-18-88 SIDE APPROACH 10-1-01 REVISED 3-28-01 REVISED REVISED STANDARD NO. MD 104.87-14 REVISED